



CLAD OUTSWING DOORS - Residential Series

Clad Outswing Doors – Residential Series

CLAD FRENCH OUTSWING DOOR; CFOD RES9, CFODSL RES9

| Glazing Description | Spacer | U-Value | R-Value | SHGC | VT | N | NC | SC | S | BTM Rail | Stiles |
|---|--------------------------|---------|---------|------|------|------|----|----|---|----------|-----------|
| No Grilles, 7/8" and 1 1/4" SDL | Insul LoE 366 W/Argon | SS | 0.29 | 3.45 | 0.17 | 0.38 | | | | 9" | 4" Stiles |
| No Grilles, 7/8" and 1 1/4" SDL | Insul LoE 366/EA w/Argon | XL | 0.27 | 3.70 | 0.16 | 0.35 | | | | 9" | 4" Stiles |
| No Grilles, 7/8" and 1 1/4" SDL | Insul LoE 240 w/Argon | SS | 0.30 | 3.33 | 0.15 | 0.23 | | | | 9" | 4" Stiles |
| Grilles in Airspace, 7/8" and 1 1/4" SDLB | Insul LoE 366 W/Argon | SS | 0.29 | 3.45 | 0.15 | 0.33 | | | | 9" | 4" Stiles |
| Grilles in Airspace, 7/8" and 1 1/4" SDLB | Insul LoE 366/EA w/Argon | XL | 0.27 | 3.70 | 0.14 | 0.30 | | | | 9" | 4" Stiles |
| Grilles in Airspace, 7/8" and 1 1/4" SDLB | Insul LoE 240 w/Argon | SS | 0.30 | 3.33 | 0.14 | 0.20 | | | | 9" | 4" Stiles |

CLAD FRENCH OUTSWING DOOR with Breather Tube; CFOD RES9, CFODSL RES9

| | | | | | | | | | | | |
|---|------------------|----|------|------|------|------|--|--|--|----|-----------|
| No Grilles, 7/8" and 1 1/4" SDL | Insul LoE 366/EA | XL | 0.29 | 3.45 | 0.16 | 0.35 | | | | 9" | 4" Stiles |
| Grilles in Airspace, 7/8" and 1 1/4" SDLB | Insul LoE 366/EA | XL | 0.29 | 3.45 | 0.14 | 0.30 | | | | 9" | 4" Stiles |

CLAD FRENCH OUTSWING DOOR; CFOD RES12, CFODSL RES12

| Glazing Description | Spacer | U-Value | R-Value | SHGC | VT | N | NC | SC | S | BTM Rail | Stiles |
|---|--------------------------|---------|---------|------|------|------|----|----|---|----------|-----------|
| No Grilles, 7/8" and 1 1/4" SDL | Insul LoE 366 W/Argon | SS | 0.30 | 3.33 | 0.16 | 0.36 | | | | 12" | 4" Stiles |
| No Grilles, 7/8" and 1 1/4" SDL | Insul LoE 366/EA w/Argon | XL | 0.28 | 3.57 | 0.15 | 0.33 | | | | 12" | 4" Stiles |
| No Grilles, 7/8" and 1 1/4" SDL | Insul LoE 240 w/Argon | SS | 0.30 | 3.33 | 0.15 | 0.22 | | | | 12" | 4" Stiles |
| Grilles in Airspace, 7/8" and 1 1/4" SDLB | Insul LoE 366 W/Argon | SS | 0.30 | 3.33 | 0.14 | 0.31 | | | | 12" | 4" Stiles |
| Grilles in Airspace, 7/8" and 1 1/4" SDLB | Insul LoE 366/EA w/Argon | XL | 0.28 | 3.57 | 0.13 | 0.28 | | | | 12" | 4" Stiles |
| Grilles in Airspace, 7/8" and 1 1/4" SDLB | Insul LoE 240 w/Argon | SS | 0.30 | 3.33 | 0.13 | 0.19 | | | | 12" | 4" Stiles |

CLAD FRENCH OUTSWING DOOR with Breather Tube; CFOD RES12, CFODSL RES12

| | | | | | | | | | | | |
|---|------------------|----|------|------|------|------|--|--|--|-----|-----------|
| No Grilles, 7/8" and 1 1/4" SDL | Insul LoE 366/EA | XL | 0.29 | 3.45 | 0.15 | 0.33 | | | | 12" | 4" Stiles |
| Grilles in Airspace, 7/8" and 1 1/4" SDLB | Insul LoE 366/EA | XL | 0.29 | 3.45 | 0.13 | 0.28 | | | | 12" | 4" Stiles |

Values in Green meet the ≤ 0.30 U value and ≤ 0.30 SHGC Tax Incentive Program requirements.

SS = Semco Foam Spacer, XL = Cardinal Stainless Spacer; Units specified with Semco Foam Spacer may at times be converted to Cardinal Stainless Spacer due to unique glass type and/or size constraints. This may or may not affect performance data.