

CLAD GLIDER

CLAD GLIDER

Glazing Description		Spacer	U-Value	R-Value	SHGC	VT	N	NC	SC	S
11/16" IG No Grilles in Airspace w/storm	Insul LoE 366 W/Argon	SS	0.25	4.00	0.22	0.43				
11/16" IG No Grilles in Airspace w/storm	Insul LoE 240 w/Argon	SS	0.25	4.00	0.22	0.26				
11/16" IG With Airspace Grilles w/storm	Insul LoE 366 W/Argon	SS	0.25	4.00	0.20	0.38				
11/16" IG With Airspace Grilles w/storm	Insul LoE 240 w/Argon	SS	0.25	4.00	0.20	0.23				

CLAD GLIDER with Breather Tube

11/16" IG No Grilles in Airspace w/storm	Insul LoE 366	SS	0.27	3.70	0.23	0.43				
11/16" IG No Grilles in Airspace w/storm	Insul LoE 240	SS	0.27	3.70	0.24	0.26				
11/16" IG With Airspace Grilles w/storm	Insul LoE 366	SS	0.27	3.70	0.21	0.38				
11/16" IG With Airspace Grilles w/storm	Insul LoE 240	SS	0.27	3.70	0.21	0.23				

Values in Green meet the ≤ 0.30 U value and ≤ 0.30 SHGC Tax Incentive Program requirements.

SS = Semco Foam Spacer, XL = Cardinal Stainless Spacer; Units specified with Semco Foam Spacer may at times be converted to Cardinal Stainless Spacer due to unique glass type and/or size constraints. This may or may not affect performance data.