

EYEBROW CASEMENT SINGLE UNIT OPENING SPECIFICATIONS

UNIT CODE	CLEAR OPENING			DAYLIGHT SQ. FT.	VENT SQ. FT.
	SQ. FT.	WIDTH	HEIGHT		
1836-1	2.7	13"	30-5/16"	2.6	2.8
1840-1	3.1	13"	34-5/16"	2.9	3.2
1848-1	3.8	13"	41-5/8"	3.5	3.9
1852-1	4.2	13"	46-5/16"	4.0	4.3
1860-1	4.8	13"	53-5/8"	4.5	4.9
1864-1	5.3	13"	58-5/16"	4.9	5.4
1872-1	5.9	13"	65-5/8"	5.5	6.0
CCE1878-1	6.5	13"	71-5/8"	6.0	6.6
2036-1	3.3	16"	29-7/8"	3.2	3.5
2040-1	3.8	16"	33-7/8"	3.6	3.9
2048-1	4.6	16"	41-3/16"	4.4	4.7
2052-1	5.1	16"	45-7/8"	4.9	5.3
2060-1	5.9	16"	53-3/16"	5.7	6.1
2064-1	6.4	16"	57-7/8"	6.1	6.6
2072-1	7.2	16"	65-3/16"	6.9	7.4
CCE2078-1	7.9	16"	71-3/16"	7.5	8.1
2436-1	3.9	19-5/16"	29-5/16"	3.9	4.2
2440-1	4.5	19-5/16"	33-5/16"	4.4	4.7
2448-1	5.4	19-5/16"	40-5/8"	5.3	5.7
2452-1	6.1	19-5/16"	45-5/16"	5.9	6.3
2460-1	7.1	19-5/16"	52-5/8"	6.9	7.3
2464-1	7.7	19-5/16"	57-5/16"	7.5	7.9
2472-1	8.7	19-5/16"	64-5/8"	8.4	8.9
CCE2478-1	9.5	19-5/16"	70-5/8"	9.2	9.7
2836-1	4.7	24"	28-9/32"	4.8	5.1
2840-1	5.4	24"	32-9/32"	5.5	5.8
u 2848-1	6.6	24"	39-19/32"	6.7	7.0
u 2852-1	7.4	24"	44-9/32"	7.4	7.8
u 2860-1	8.6	24"	51-19/32"	8.6	9.0
u 2864-1	9.4	24"	56-9/32"	9.3	9.8
u 2872-1	10.6	24"	63-19/32"	10.5	11.0
CCE2878-1	11.6	24"	69-19/32"	11.5	12.0
3236-1	5.3	28"	27-5/32"	5.6	5.9
u 3240-1	6.1	28"	31-5/32"	6.4	6.7
u 3248-1	7.5	28"	38-15/32"	7.7	8.1
u 3252-1	8.4	28"	43-5/32"	8.6	9.0
u 3260-1	9.8	28"	50-15/32"	10.0	10.4
u 3264-1	10.7	28"	55-5/32"	10.9	11.4
u 3272-1	12.1	28"	62-15/32"	12.3	12.8
CCE3278-1	13.3	28"	68-15/32"	13.4	13.9
u 3636-1	5.7	31-5/16"	26-1/16"	6.2	6.5
u 3640-1	6.5	31-5/16"	30-1/16"	7.1	7.4
u 3648-1	8.1	31-5/16"	37-3/8"	8.6	9.0
u 3652-1	9.1	31-5/16"	42-1/16"	9.6	10.0
u 3660-1	10.7	31-5/16"	49-3/8"	11.2	11.6
u 3664-1	11.8	31-5/16"	54-1/16"	12.1	12.6
u 3672-1	13.3	31-5/16"	61-3/8"	13.7	14.2
CCE3678-1	14.7	31-5/16"	67-3/8"	15.0	15.5

- u These units meet egress using the following requirements:
 20-inch minimum clear opening width.
 24-inch minimum clear opening height.
 5.7 square feet minimum.
 Check local building codes for exact specifications.

EYEBROW CASEMENT DOUBLE UNIT OPENING SPECIFICATIONS

UNIT CODE	CLEAR OPENING			DAYLIGHT SQ. FT.	VENT SQ. FT.
	SQ. FT.	WIDTH	HEIGHT		
1836-2	2.6	13"	29-11/32"	2.5	2.8
1840-2	3.0	13"	33-11/32"	2.9	3.2
1848-2	3.7	13"	40-21/32"	3.5	3.8
1852-2	4.1	13"	45-11/32"	3.9	4.2
1860-2	4.8	13"	52-21/32"	4.5	4.9
1864-2	5.2	13"	57-11/32"	4.9	5.3
1872-2	5.8	13"	64-21/32"	5.5	6.0
CCE1878-2	6.4	13"	70-21/32"	6.0	6.5
2036-2	3.2	16"	28-3/8"	3.1	3.4
2040-2	3.6	16"	32-3/8"	3.5	3.8
2048-2	4.4	16"	39-11/16"	4.3	4.7
2052-2	4.9	16"	44-3/8"	4.8	5.2
2060-2	5.7	16"	51-11/16"	5.6	6.0
2064-2	6.3	16"	56-3/8"	6.1	6.5
2072-2	7.1	16"	63-11/16"	6.8	7.3
CCE2078-2	7.7	16"	69-11/16"	7.5	8.0
2436-2	3.6	19-5/16"	27-3/32"	3.8	4.1
2440-2	4.2	19-5/16"	31-3/32"	4.3	4.6
2448-2	5.2	19-5/16"	38-13/32"	5.2	5.6
2452-2	5.8	19-5/16"	43-3/32"	5.8	6.2
2460-2	6.8	19-5/16"	50-13/32"	6.7	7.2
2464-2	7.4	19-5/16"	55-3/32"	7.3	7.8
2472-2	8.4	19-5/16"	62-13/32"	8.3	8.8
CCE2478-2	9.2	19-5/16"	68-13/32"	9.0	9.6
2836-2	4.1	24"	24-7/8"	4.6	4.9
2840-2	4.8	24"	28-7/8"	5.2	5.6
u 2848-2	6.0	24"	36-3/16"	6.4	6.8
u 2852-2	6.8	24"	40-7/8"	7.2	7.6
u 2860-2	8.0	24"	48-3/16"	8.3	8.8
u 2864-2	8.8	24"	52-7/8"	9.1	9.6
u 2872-2	10.0	24"	60-3/16"	10.3	10.8
CCE2878-2	11.0	24"	66-3/16"	11.2	11.8
3236-2	4.4	28"	22-1/2"	5.3	5.6
3240-2	5.2	28"	26-1/2"	6.0	6.4
u 3248-2	6.6	28"	33-13/16"	7.4	7.8
u 3252-2	7.5	28"	38-1/2"	8.3	8.7
u 3260-2	8.9	28"	45-13/16"	9.6	10.1
u 3264-2	9.8	28"	50-1/2"	10.5	11.0
u 3272-2	11.2	28"	57-13/16"	11.9	12.5
CCE3278-2	12.4	28"	63-13/16"	13.0	13.6
3636-2	4.4	31-5/16"	20-3/16"	5.7	6.1
3640-2	5.3	31-5/16"	24-3/16"	6.6	7.0
u 3648-2	6.8	31-5/16"	31-1/2"	8.1	8.5
u 3652-2	7.9	31-5/16"	36-3/16"	9.1	9.1
u 3660-2	9.5	31-5/16"	43-1/2"	10.7	11.2
u 3664-2	10.5	31-5/16"	48-3/16"	11.7	12.2
u 3672-2	12.1	31-5/16"	55-1/2"	13.2	13.8
CCE3678-2	13.4	31-5/16"	61-1/2"	14.1	15.1

NOTE

Due to continued research toward superior products – specifications, features, and design are subject to change without notification.