

PUSH-OUT FRENCH CASEMENT OPENING SPECIFICATIONS

UNIT CODE	CLEAR OPENING			DAYLIGHT SQ. FT.	VENT SQ. FT.
	SQ. FT.	WIDTH	HEIGHT		
2036-2	5.3	25-1/2"	29-7/8"	6.5	7.1
2040-2	6.0	25-1/2"	33-7/8"	7.3	8.0
2048-2	7.3	25-1/2"	41-3/16"	8.9	9.8
2052-2	8.1	25-1/2"	45-7/8"	9.8	10.9
2060-2	9.4	25-1/2"	53-3/16"	11.4	12.6
2064-2	10.2	25-1/2"	57-7/8"	12.4	13.7
2072-2	11.5	25-1/2"	65-3/16"	13.9	15.4
2436-2	6.6	31-11/16"	29-7/8"	7.9	8.5
2440-2	7.5	31-11/16"	33-7/8"	8.9	9.6
2448-2	9.1	31-11/16"	41-3/16"	10.8	11.7
2452-2	10.1	31-11/16"	45-7/8"	12.0	13.0
2460-2	11.7	31-11/16"	53-3/16"	13.9	15.1
2464-2	12.7	31-11/16"	57-7/8"	15.1	16.4
2472-2	14.3	31-11/16"	65-3/16"	16.9	18.4
2836-2	8.4	40-1/2"	29-7/8"	9.9	10.4
2840-2	9.5	40-1/2"	33-7/8"	11.2	11.8
2848-2	11.6	40-1/2"	41-3/16"	13.6	14.3
2852-2	12.9	40-1/2"	45-7/8"	15.1	16.0
2860-2	15.0	40-1/2"	53-3/16"	17.4	18.5
2864-2	16.3	40-1/2"	57-7/8"	18.9	20.1
2872-2	18.3	40-1/2"	65-3/16"	21.3	22.7

NOTE: Clear opening and vent opening based on both sash open.
2036-2 does not meet egress.

ALL PUSH-OUT FRENCH CASEMENT, WITH THE EXCEPTION OF
2036-2, MEET EGRESS REQUIREMENTS.

Check local building codes for exact specifications.

NOTE

Due to continued research toward superior products – specifications, features, and design are subject to change without notification.