

FRENCH IN-SWING DOOR OPENING SPECIFICATIONS

STANDARD SILL

UNIT CODE	CLEAR OPENING			CLEAR OPENING			DAYLIGHT SQ. FT.	DAYLIGHT COMMERCIAL	VENT. SQ. FT.
	SQ. FT.	WIDTH	HEIGHT	SQ. FT.	WIDTH	HEIGHT			
R2668	14.0	25-9/16"	79-1/16"				8.8	6.6	14.0
26610	18.0	28"	92-9/16"				10.3	8.0	18.0
2680	14.9	28"	76-9/16"				12.4	9.6	14.9
R3068	17.3	31-9/16"	79-1/16"				11.6	9.2	17.3
30610	21.9	34"	92-9/16"				13.2	10.7	21.9
3080	18.7	34"	79-1/16"				15.8	12.9	18.7
40610	14.1	21-15/16"	92-9/16"	28.4	44-3/16"	92-9/16"	15.1	10.5	28.4
4080	11.7	21-15/16"	76-9/16"	23.5	44-3/16"	76-9/16"	18.1	12.6	23.5
R5068	14.0	25-1/2"	79-1/16"	28.2	51-5/16"	79-1/16"	17.7	13.2	28.2
50610	18.0	27-15/16"	92-9/16"	36.1	56-3/16"	92-9/16"	20.7	15.9	36.1
5080	15.3	27-15/16"	79-1/16"	30.8	56-3/16"	79-1/16"	24.8	19.2	30.8
R6068	20.2	31-1/2"	92-9/16"	40.7	63-5/16"	92-9/16"	23.4	18.4	40.7
60610	18.6	33-15/16"	79-1/16"	37.4	68-3/16"	79-1/16"	26.3	21.4	37.4
6080	21.8	33-15/16"	92-9/16"	43.8	68-3/16"	92-9/16"	31.6	25.8	43.8
Active panel open to 90°				Both panels open to 90°				Clad only	

FRENCH IN-SWING DOOR OPENING SPECIFICATIONS

LOW PROFILE, HANDICAP ACCESSIBLE SILL

UNIT CODE	CLEAR OPENING			CLEAR OPENING			DAYLIGHT SQ. FT.	DAYLIGHT W/12" BOTTOM RAIL	DAYLIGHT COMMERCIAL	DAYLIGHT COM. W/12" BOTTOM RAIL	VENT. SQ. FT.
	SQ. FT.	WIDTH	HEIGHT	SQ. FT.	WIDTH	HEIGHT					
26610	15.7	28"	80-13/16"				10.3	9.9	8.0	7.6	15.7
2680	18.3	28"	94-5/16"				12.4	11.9	9.6	9.2	18.3
30610	19.1	34"	80-13/16"				13.2	12.6	10.7	10.2	19.1
3080	22.3	34"	94-5/16"				15.8	15.2	12.9	12.4	22.3
50610	15.7	27-15/16"	80-13/16"	31.6	56-1/4"	80-13/16"	20.7	19.7	15.9	15.2	31.6
5080	18.3	27-15/16"	94-5/16"	36.8	56-1/4"	94-5/16"	24.8	23.9	19.2	18.5	36.8
60610	19.0	33-15/16"	80-13/16"	38.3	68-1/4"	80-13/16"	26.3	25.1	21.4	20.4	38.3
6080	22.2	33-15/16"	94-5/16"	44.7	68-1/4"	94-5/16"	31.6	30.4	25.8	24.8	44.7
Active panel open to 90°				Both panels open to 90°				Commercial available in clad only			

CLAD FRENCH OUT-SWING DOOR OPENING SPECIFICATIONS

LOW PROFILE SILL WITH SILL STOP

UNIT CODE	CLEAR OPENING			CLEAR OPENING			DAYLIGHT SQ. FT.	DAYLIGHT W/12" BOTTOM RAIL	DAYLIGHT COMMERCIAL	DAYLIGHT COM. W/12" BOTTOM RAIL	VENT. SQ. FT.
	SQ. FT.	WIDTH	HEIGHT	SQ. FT.	WIDTH	HEIGHT					
26610	15.5	28"	79-11/16"				10.3	9.9	8.0	7.6	15.5
2680	18.1	28"	93-3/16"				12.4	11.9	9.6	9.2	18.1
30610	18.8	34"	79-11/16"				13.2	12.6	10.7	10.2	18.8
3080	22.0	34"	93-3/16"				15.8	15.2	12.9	12.4	22.0
40610	12.2	22"	79-11/16"	24.5	44-5/16"	79-11/16"	15.1	14.4	10.5	10.0	24.5
4080	14.2	22"	93-3/16"	28.7	44-5/16"	93-3/16"	18.1	17.4	12.6	12.2	28.7
50610	15.5	28"	79-11/16"	31.2	56-5/16"	79-11/16"	20.7	19.7	15.9	15.2	31.2
5080	18.1	28"	93-3/16"	36.4	56-5/16"	93-3/16"	24.8	23.9	19.2	18.5	36.4
60610	18.8	34"	79-11/16"	37.8	68-5/16"	79-11/16"	26.3	25.1	21.4	20.4	37.8
6080	22.0	34"	93-3/16"	44.2	68-5/16"	93-3/16"	31.6	30.4	25.8	24.8	44.2
Active panel open to 90°				Both panels open to 90°							

FRENCH SWINGING DOOR

CLAD FRENCH OUT-SWING DOOR OPENING SPECIFICATIONS

LOW PROFILE SILL WITH NO SILL STOP AND 12" BOTTOM RAIL

UNIT CODE	CLEAR OPENING			CLEAR OPENING			DAYLIGHT SQ. FT.	DAYLIGHT COMMERCIAL	VENT. SQ. FT.
	SQ. FT.	WIDTH	HEIGHT	SQ. FT.	WIDTH	HEIGHT			
26610	15.7	28"	80-9/16"				9.9	7.6	15.7
2680	18.3	28"	94-1/16"				11.9	9.2	18.3
30610	19.0	34"	80-9/16"				12.6	10.2	19.0
3080	22.2	34"	94-1/16"				15.2	12.4	22.2
40610	12.3	22"	80-9/16"	24.8	44-5/16"	80-9/16"	14.4	10.0	24.8
4080	14.4	22"	94-1/16"	28.9	44-5/16"	94-1/16"	17.4	12.2	28.9
50610	15.7	28"	80-9/16"	31.5	56-5/16"	80-9/16"	19.7	15.2	31.5
5080	18.3	28"	94-1/16"	36.8	56-5/16"	94-1/16"	23.9	18.5	36.8
60610	19.0	34"	80-9/16"	38.2	68-5/16"	80-9/16"	25.1	20.4	38.2
6080	22.2	34"	94-1/16"	44.6	68-5/16"	94-1/16"	30.4	24.8	44.6
Active panel open to 90°			Both panels open to 90°						

WOOD FRENCH OUT-SWING DOOR OPENING SPECIFICATIONS

LOW PROFILE SILL WITH SILL STOP

UNIT CODE	CLEAR OPENING			CLEAR OPENING			DAYLIGHT SQ. FT.	DAYLIGHT W/12" BOTTOM RAIL	VENT. SQ. FT.
	SQ. FT.	WIDTH	HEIGHT	SQ. FT.	WIDTH	HEIGHT			
26610	15.5	28"	79-15/16"				10.3	9.9	15.5
2680	18.2	28"	93-7/16"				12.4	11.9	18.2
30610	18.9	34"	79-15/16"				13.2	12.6	18.9
3080	22.1	34"	93-7/16"				15.8	15.2	22.1
40610	12.2	22"	79-15/16"	24.6	44-5/16"	79-15/16"	15.1	14.4	24.6
4080	14.3	22"	93-7/16"	28.8	44-5/16"	93-7/16"	18.1	17.4	28.8
50610	15.5	28"	79-15/16"	31.3	56-5/16"	79-15/16"	20.7	19.7	31.3
5080	18.2	28"	93-7/16"	36.5	56-5/16"	93-7/16"	24.8	23.9	36.5
60610	18.9	34"	79-15/16"	37.9	68-5/16"	79-15/16"	26.3	25.1	37.9
6080	22.1	34"	93-7/16"	44.3	68-5/16"	93-7/16"	31.6	30.4	44.3
Active panel open to 90°			Both panels open to 90°						

WOOD FRENCH OUT-SWING DOOR OPENING SPECIFICATIONS

LOW PROFILE SILL WITH NO SILL STOP AND 12" BOTTOM RAIL

UNIT CODE	CLEAR OPENING			CLEAR OPENING			DAYLIGHT SQ. FT.	VENT. SQ. FT.	
	SQ. FT.	WIDTH	HEIGHT	SQ. FT.	WIDTH	HEIGHT			
26610	15.7	28"	80-13/16"				9.9	15.7	
2680	18.3	28"	94-5/16"				11.9	18.3	
30610	19.1	34"	80-13/16"				12.6	19.1	
3080	22.3	34"	94-5/16"				15.2	22.3	
40610	12.3	22"	80-13/16"	24.9	44-5/16"	80-13/16"	14.4	24.9	
4080	14.4	22"	94-5/16"	29.0	44-5/16"	94-5/16"	17.4	29.0	
50610	15.7	28"	80-13/16"	31.6	56-5/16"	80-13/16"	19.7	31.6	
5080	18.3	28"	94-5/16"	36.9	56-5/16"	94-5/16"	23.9	36.9	
60610	19.1	34"	80-13/16"	38.3	68-5/16"	80-13/16"	25.1	38.3	
6080	22.3	34"	94-5/16"	44.7	68-5/16"	94-5/16"	30.4	44.7	
Active panel open to 90°			Both panels open to 90°						